



SMT-3215

32" LED monitor



Key Features

- 32 inch FHD Monitor, support up to 1920×1080 @60Hz
- Brightness 300 cd/m² (Typical), Contrast 3200:1 (Minimum) 4000:1 (Typical)
- Viewing Angle (H/V) : 178°/178°, Response Time : 20ms (Typical)
- Video Input : HDMI, DP, VGA
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

SMT-3215

32" LED monitor



Specifications

Display	
Type	LED Monitor
Screen Size	31.5"
Max. Resolution	1920*1080 60Hz (FHD)
Brightness	300 cd/m ² (Typ)
Contrast Ratio	3200:1 (Min) 4000:1 (Typ)
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	16.7M
Response Time	20ms(Typ)
Panel Life	30,000 hours

Interface		
Video	Connectors	VGA (1) HDMI 1.4(1), DP 1.2(1) Audio-in(1) Audio-out (1)
VGA	Connector	1port Analog D-sub(15 pin)
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
HDMI	Connector	HDMI
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
DP	Connector	DP
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
Audio	Connector	Audio in/out
	Output Signal	Loop-through line level(PC only), Speakers : 4Ω 2.5Wx 2

On Screen Display	
Functions	VESA™ DPM Compatible
Language	Korean, English, Русский, Deutsch, Français, Español, Italiano, Português, Chinese (Simplified), Chinese (Traditional), Japanese, Arabic

General	
---------	--

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com.

Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	<60W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions with Stand (WxHxD)	714.0*484.2*200.8mm
	Dimensions without Stand (WxHxD)	714.0*423.7*53.7mm
	Weight	7.28kg(with stand), 5.9Kg(without stand)
	Cabinet Color	Black
	VESA Mounts Interface	100 x 100mm