



User Manual

CGW - M2I



www.commax.com

COMMAX Co., Ltd.



- $\bullet\,$ Thank you for purchasing COMMAX products.
- Please carefully read this User's Guide (in particular, precautions for safety) before using a product and follow instructions to use a product exactly.
- The company is not responsible for any safety accidents caused by abnormal operation of the product.



Greetings	1
Warnings and Cautions	
Product Configuration & Name	
Using mobile application	
Check CCTV Image	
Receive call from mobile phone	
Product specification	



1. Greetings

- Thank you for Purchasing COMMAX Products
- Please carefully read this User's Manual (in particular, precautions for safety) before using a product and follow instructions to use a product exactly.



2. Warnings and cautions

Please follow the things described below in order to prevent any danger or property damage.



Narnina

It may cause a serious damage or injury if violated.



Caution

It may cause a minor damage or injury if violated.



Prohibition.



No disassembly



No touch



Must follow strictly.



Shows plugging out the power cord without an exception

Shows the warning and caution for a fire.



Shows the warning and caution for an electric shock.

Please don't use several products at the same time on one power socket.

It may cause a fire due to an abnormal overheating.




Please don't bend the power cable excessively or it may cause an electric shock.

· fire when using a damaged power cable.





Please don't handle the power cable with a wet hand. · It may cause an electric shock.






Please plug out the power cable from the socket when not using it for a long period of time.

· It may shorten the product lifespan or cause a fire.



Please don't install the product in the place where there is much oil, smoke or humidity.

· It may cause an electric



Please don't install the product with the lightening and thunder.

· It may cause an electric shock or fire.



Please don't use and connect this product with other products with different rated voltage

· It may cause a disorder or



that generates heat, please install the product away from the wall (10cm) for the ventilation.

When installing the product

· It may cause a fire due to the increased internal temperature.



2

Warning

Please don't disassemble, repair or rebuild this product arbitrarily (please contact the service center if a repair is needed. shock or fire.

Cleaning & Use

· It may cause an electric



If an abnormal sound, burning smell or smoke is coming out of the product, please plug out the power cable and contact a service center.

It may cause an electric shock or fire.



Please don't insert any metallic or burnable materials into the ventilation hole.

· It may cause an electric shock or fire.



rohibition Electric shock

When connecting the power

cables after cutting the cable,

please install the product with


· It may cause an electric

power off

shock or fire

Please use only the designated batteries for the products of using DC power.

· It may cause an electric shock or fire.






Caution

Please plug the power cable firmly into the inner end

· It may cause a fire.



Please hold the plug tightly when unplugging the power cable (a part of the copper wire may be disconnected if the grabbing is only made on the cord when pulling out the cable).

· It may cause an electric shock or fire





Please check the use voltage and current for the DC-only

Please avoid direct rays of the sun or heating devices at a time of installation.


Electric shock

· It may cause a fire.



When installing the product, please fix it firmly while using the wall-mounting unit and screws. · It may cause an injury from

the falling object.



Please don't install the product on an unstable place or small support board.

· It may cause an injury if it falls down while in use.



Please be careful when using an AC circuit breaker since there is a possibility of an electric shock.



When cleaning the product,

please rub it with a soft and

dry cloth after plugging out

the power cable. (Please

don't use any chemical

products such as wax.

benzene, alcohol or cleanser.)

Prohibition

products and use the appropriate rectifier. · It may cause a fire.



Please don't drop the product on the ground and don' t apply a shock.

· It may cause a failure.



Please use the designated connection cable within the maximum calling distance designated for the product


· It may reduce the product performance.



Cleaning & Use


Power & Installation







PRODUCT CONFIGURATION & NAME



No.	DESCRIPTION	No.	DESCRIPTION
1	LAN CONNECTION PORT	3	CMD-101BU
'			CONNECTION PORT
2	POWER ADAPTOR	4	CMD-404FU
	(14V/2.1A)		CONNECTION PORT



Chapter 2. Using mobile application



**The application can be used free of charge when connected to Wi-Fi, but if not, data usage charges can be imposed according to data payment system.



Using mobile application

- 1) Start 'COMMAX' application.
- 2) Press 'PIN Start' button.



- 5) Input room information into 'ROOM NUMBER' menu.
- 6) Input 'PASSWORD'.
- ※ (Default 'PASSWORD' is '1234'.)
- 7) Press 'NEXT' button.



- 3) Input "PIN" number. (ex: 6977 5174 5837)
- 4) Press 'NEXT' button.
- *The PIN number sticker is attached on the product.



- 8) Input 'NEW PASSWORD'.
- 9) Press 'NEXT' button.
- * Default password must be changed.
- * Password '1234' cannot be used.





Check CCTV Image

1) Click 'CCTV' button from the list.



2) Click the CCTV list that you want (ex: CCTV1 Channel)



3) CCTV Image shown on the screen that you select.

4) If you click 'STOP' button, CCTV Image will be over.





*You cannot concurrent access to CCTV Image

If "Network error or other user watching the CCTV" message on the screen, you can access
after a while.



Receive call from mobile phone

1) Click 'CCTV' button from the list.



2) Click the CCTV list that you want (ex: CCTV1 Channel)





Set-up

1) Click 'Set-up' button from the list.



- 2) You can change the password when you click 'password change' button.
- 3) If you click 'log-out' button, APP will be closed.





Model Specification	CGW-M2I		
Transmission	Ethernet(LAN): CAT 5e		
Halisillission	CMD-101BU / CMD-404FU: 8 wires Polarity (RJ45 CAT5e Patch Cable)		
Power source DC 14V / 2.1A(Max)			
Wiring Distance	Modum System Wiring Distance (MAX 300m)		
	Wiring Procedure : CMD-101BU → "CGW-M2I" → CMD-404FU		
	* It is advisable to follow the above wiring procedure because CGW-M2I is close to CMD-101BU.		
Operating temp.	-10°C~ +40°C		
Dimension	122(w) x 76(D) x 48(H) mm		



COMMAX Co.,Ltd.

513-11, Sangdaewon-dong, Jungwon-gu, Seongnam-si, Gyeonggi-do, Korea Int'l Business Dept. Tel.: +82-31-7393-540~550 Fax.: +82-31-745-2133

Web site: www.commax.com

PM56M2100010 Printed In Korea / 2015.06.104