

Tonmind 15W IP Horn Speaker SIP-S21

1. Produce loud and excellent sound.
2. IP67 waterproof design for installation in outdoors.
3. PoE eliminates need for local power supply.
4. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
5. Compatible with IP Camera VMS via ONVIF.
6. Support Pre-recorded messages.
7. Support HPPT API for alarm in transmit.



Specification:

Audio

Decoding: OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Speaker

Max SPL: 113dB

Frequency Response: 300Hz~8KHz

Frequency Range: 500-2KHZ +-10dB
400-12KHZ +-20dB

Harmonic Distortion: 0.1@1kHz

Signal to Noise Ratio: 91dB

Network

Security: Password protection, IP address filtering, Digest authentication, User access log, firewall

Network Protocol: SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP

Network Interface: 10/100 Base-TX, RJ45

Support for SIP protocol for intergration with VoIP systimes, intergrated with SIP/PBX.

VoIP: Support SIP features: secondary/backend SIP server, IPv4 (IPv6 futhur)

Support codecs: OPUS, G711U, G711A, GSM, MP3

Amplifier

Amplifier Description: Built-in 15W Amplifier

General

Operating Temperature: -30°C — +60°C

Operating humility: 5%-85%

Material: ABS (IP67 water-proof)

Rate Power: 15W

Power Supply: PoE or 12V

Installation: Wall Mounted

Dimensions: 285*205*290mm

Net Weight: 1.3 KG

Languages: English

Warranty: 2 years

Package Includes: IP Horn Speaker
User Manual